



Worldwide Presence
Engineering Expertise
Leading Edge Technology
Award Winning Support
Our Commitment to Quality



High Frequency Magnetics At-A-Glance

Your one source for wire wound
magnetic solutions

High Frequency Magnetics
Switching Transformers
SMD Power Inductors
Inductors / Chokes
Line Filters
Drum Core Inductors
PoE Transformers
PoDL Transformers



+1 866.239. 5777
belfuse.com/signal

Whatever stage your product's development is in and you need magnetics, we have the right solution for you. Signal Transformer... is your one source.

MEDICAL

Diagnostic
Surgical Equipment
Patient Monitoring
Hand Held Devices
Surgical Generators
In-Home Dialysis
Blood Analyzers

NETWORKING

Data Center Switching
Routers
Servers & Server I/O
Server Blades
100G Core Switches
NIC Cards
3U Top Rack & End of Rack
40G Firewall
Patch Panels & Wiring
Closet

TELECOM/DATACOM

Set-Top Boxes
Hard Drives
Laptops
Printers
Plotters
PBX
Current Line Detection

FIRE/SECURITY

High Speed Cable Assy
Terminal Blocks
Coax Connectors
D-Sub Connectors
Z Axis Compress Interfacing
Circular Connectors
Card Edge Connectors
Power Connectors

TRANSPORTATION

E-Mobility
Off Road
Automotive
Aerospace
Agriculture
Construction
Material Handling
Marine
Stationary Engines
Engine Control


Platforms For Switching Regulators

- EE/EI/EP/EFD/EER/ER/EF/UI /RM/PQ/U
- 20 kHz to 500 kHz Operating Frequency
- 0.5 W to 600 W Power Capacity Range



PoE & PoDL* - Power over Ethernet & Data Lines

- PoE - 3 W to 15 W Rated Power
- PoE - EP7, EP10, EP13 SMT Platforms
- PoDL - 40 Ω - 2500 Ω Impedance
- PoDL - 0.9 A to 15 A Rated Current
- 1500 V_{DC} Isolation, -40°C to 125°C Operating Temp.



PQ Core Platform DC-DC Converter

- 20 kHz to 250 kHz Operating Frequency
- 9 W to 600 W Power Capacity Range
- Through Hole Mount Vertical



RM Core Platform DC-DC Converter

- 20 kHz to 250 kHz Operating Frequency
- 2 W to 250 W Power Capacity Range
- Through Hole Mount or SMT Package




EFD & ETD Core Platform DC-DC Converter

- 100 kHz to 500 kHz Operating Frequency
- EFD - 4 W to 60 W Power Capacity Range
- ETD - 36 W to 150 W Power Capacity Range
- Through Hole Mount or SMT Package



EE Core Platform DC-DC Converter

- 100 kHz to 300 kHz Operating Frequency
- 0.5 W to 200 W Power Capacity Range
- Through Hole Mount or SMT Package




EP Core Platform DC-DC Converter

- 100 kHz to 300 kHz Operating Frequency
- 0.9 W to 18 W Power Capacity Range
- Through Hole Mount or SMT Package



Signal Transformer products are utilized in all segments of the electronics spectrum.




EPC Core Platform for DC-DC Converter

- 500 kHz Operating Frequency
- 5.5 W to 58 W Power Capacity Range
- Through Hole Mount or SMT Package




ER & EER Core Platform for DC-DC Converter

- 300 kHz to 500 kHz Operating Frequency
- 0.7 W to 180 W Power Capacity Range
- Through Hole Mount or SMT Package



High Current Toroidal Inductors for Power Supplies

- 300 kHz to 500 kHz Operating Frequency
- 2.4 A to 20 A Rated Current
- 10 μ H to 1000 μ H @ 0 A_{DC} Inductance Range
- Through Hole Mount, Horizontal or Vertical




ET, UT & U Core - Choke / Line Filters

- 0.20 mH to 100 mH Rated Inductance
- 0.3 A to 10 A Rated Current
- Through Hole Mount, Horizontal or Vertical



Drum Core* - Inductor

- 1 μ H to 2750 μ H Rated Inductance
- 8.4 mA to 95 A Rated Current
- Through Hole Mount, Available in Tape and Reel



Toroid Core CM Chokes / Filters Inductors

- 10 mH to 100 mH Rated Inductance
- 0.3 A to 20 A Rated Current
- Through Hole Mount, Horizontal or Vertical



SMD* Power Inductors

- 0.01 μ H to 10 mH Rated Inductance
- 4 mA to 70 A Rated Current
- 1mm to 12.3 mm Rated Height Range

POWER MODULES

- Std Brick Converters
- Non-Isolated POL Modules
- Voltage Regulator Modules
- Power Sequencers
- Boost Converters
- Tracking Converters
- Tunable Loop™

CIRCUIT PROTECTION

- Glass Fuse
- Ceramic Fuse
- Axial Leaded Fuses
- Radial Thru Hole
- PTC Resettable Fuse
- Ultra mini SMT Fuses
- Thermal Fuse

WIRE WOUND MAGNETICS

- SMD Power Inductors
- Single Phase
- Three Phase
- Class 2
- Class II
- Buck Boost
- Linear Transformers
- Toroidal Transformers
- Auto Transformers
- Switchmode Transformer
- Drum Core Inductor
- Wireless Charging Coils

INTERCONNECT

- High Speed Cable Assy
- Terminal Blocks
- Coax Connectors
- D-Sub connectors
- Z Axis Compress Interfacing
- Circular Connectors
- Card Edge Connectors
- Power Connectors

ETHERNET CONNECTIVITY

- Harmonica Jacks
- Cable Jacks
- Plugs
- Stack Jacks
- Shielded
- Vertical & R/A Jacks
- Pwr over Ethernet Modules
- Gigabit Ethernet
- 10/100 Base -TX
- 10 Base-T
- RJ Point Five
- PoE & PoDL



Local Support

Our regional sales offices are ready to provide expert application and sales support.

In addition, our extensive network of manufacturers' representatives and distributors bring our products to you.

Please call for locations of sales offices near you or visit our website at belfuse.com/signal

Signal Transformer

128 Atlantic Avenue
Lynbrook, NY 11563
Toll-Free +1 866.239.5777
T +1 516.239.5777
F +1 516.239.7208
sales@signaltransformer.com
techhelp@signaltransformer.com